Dyna Stretch & Seal

Self Fusing Tape

Emergency Pipe Repair

- **A SELF FUSING TAPE FOR SEALING WHERE HIGH AND LOW TEMPERATURE STABILITY IS NEEDED AND FOR SEALING UNDER PRESSURE UP TO 11 BAR. RECOMMENDED AS AN EMERGENCY REPAIR BANDAGE OR WHERE MOISTURE, WEATHER AND RADIATION RESISTANCE IS REQUIRED**
- **EASY BUILD-UP - FUSES TO ITS SELF, WHICH ALLOWS THE AREA TO BE BUILT UP BY OVER WRAPPING**

FEATURES AND BENEFITS

- Seals instantly and even under pressure up to 11 bar
- Resists a Range of Temperatures & Weathering - Durable suitable for a range of service conditions
- Watertight - Excellent moisture resistance and can be applied fully submerged
- Excellent Electrical Insulation Properties - Can also be used for electrical applications with low to medium voltages



AREAS OF USE

- Pipe and cable materials
- Copper
- Steel
- Other metals
- PVC Plastic
- Rubber hoses
- Rubber cables

APPLICATION

- Indoor or outdoor
- Mechanical or electrical
- Water pipe repair
- Sealing or waterproofing cables

TECHNICAL DATA

Pressure Resistance	11bar (160 psi)
Tensile Strength	8.3 N/mm2
Elongation	325% Breaking
Thermal Stability	-90°C to 260°C continuous
Dielectric Strength	400VPM
Tear Resistance	0.86 N/mm2
UV Resistance	Highly UV resistant
Hardness Shore A	55-65
Ozone Resistance	Highly ozone resistant
Flammability	Self Extinguishing UL standard 94 rating V-0. Tested to IEEE383 and IEEE1212 for flammability - self extinguishes and will not propagate a flame Standard Compliance BS EN50393:2006, STM D2240, A-A-59163, ASTM D-149, ASTM D-412, MIL-I-46852, ASTM D2148, ASTM D3767; NEMA Class "H"
COMPLEMENTARY PRODUCTS	Aqua Stick 572-0-0500 Mega Copper Stick 704026

For more Technical Data, please refer to Safety Data Sheet of the product

NCH AUSTRALIA PTY. LTD. (ABN 19 000 609 316)
5-9 Ralph Street, Alexandria, NSW 2015
T +61 2 9669 0260 **F** +61 2 9693 1562 **www.nchaustralia.com**
©NCH Corporation 2016